John Quaif AI0112 Qualified RPII/PIPA Tester for inflatables and games.

## INSPECTION REPORT



Paul Quaif AI0113 Qualified RPII/PIPA Tester for inflatables and games.

Unit 28, Forest Business Park, Argall Avenue, London, E10 7FB Email: paulquaif58@gmail.com

Website: www.pjentertainments.co.uk

Office: 0208 509 0150 Paul: 07966 375 570 John: 07966 375 571

Office.	0206 50	19 0130 Paul: 0790	0 3/3 3/0	JOIIII: 07500	3/3 3/1		
Company Name Fax OA	11 PUI	ERMANHEROTS	Address	rolf	INFERS		
Telephone No 0807	50	[ FNO 120					
Telephone No 08780 113993 WEST ENO PO Email OPPICE @ FUNDAY LTD COM TIPTREE COS OQL							
Torrice a rowing righter. I miles des out							
Serial No:   P394-01			Date of Inspection: 22-65-24				
Name of Inspector: PAUL QUAIF		Expiry Date of Inspection: 21 -05-25					
Inflatable Type: GA				Size (L x W x H) (m) 8.6 x 8.6 x 0.62			
67417	NE LAST ONE STANDING BEDO			Size (L x W x H) (m) 8.6 x 8.6 x 0.62			
			Date of Manufacture 2019				
,	O ICE	7 100			2017		
Structure And			norage		Blower		
Seams and webbing Condition of ancho			r points	· /	Suitability		
Bed panels and steps firm		Type of anchor point PUC TRIANG			Inlet and outlet mesh		
Walls and towers firm /√	IA_	Number of anchors		16 /	Cable and plug		
rounding Alli 100 85 KG Anchor accessories				1	Impeller		
Sharp angles	Structural Materials				Return flap		
Pressure (water gauge) 14-8 Zips				PAT test IN-HOUSE			
Entrapment	1	Ropes		NA	Blower type/electric		
Stability	1	Windows/netting		NIA	Motor cover/casing		
Deflation / evacuation time SI			ides	,	Inhouse tested (PAT)		
Air loss	V	Slide platform heigh			Blower size (Hp) 2_HP		
Check toys/obstacles	A	Height of walls (1st no)			Blower tube length (m) 2.85		
Markings LASA	/	Height of walls (m)	4		Number of blowers (this unit)		
Identification LASS	V/ 18/5-		_		Petrol blowers only (4hp)		
Art work (no significant peeling)		Clamber net/foam/ladder			Play Area (L x W) (m) 8:6 DiAM		
Fall off height (m) 062 Sli		Slide sheet			Number of users and user height		
Open side fall off height (m) 0 62		Totally Enclo	osed Structu	re	Maximum user height (m) 8		
Step and ramp size (m)	A	Exits and markings			Maximum users at 1.0m		
Internal wall height (m)	IA	Deflation of user ar	ea ea		Maximum users at 1.2m 8  Maximum users at 1.5m 8		
Stitching		Pressure or user are	ea \		Maximum users at 1.5m		
Trough depth 7/44cm					Maximum users at 1.8		
Fabric (fire retardant)		INSPECTION	ON RESULTS		Customise max user height		
Fabric (strength)	4	PASS			Maximum users at customised		
Thread (non-rotting)	1	FAIL			height		
District							
Notes/Risk Assessment: THIS UNIT MUST BE SUPERVISED					Signature of tester		
BY A COMPETDANT PERSON WHICST IN OPERATION					Paul Quaif		
					John Quaif		

## Comments:

This unit must always be used with 2-inch thick, high-density crash mats on all entrances and exits at a minimum of 1.2m from the unit.

DO NOT operate in wind speeds in excess of 24mph/38kph.

This unit must always be supervised by a competent adult who is capable of exercising authority over the users.

I certify that the above equipment has been inspected to RPII standards as indicated and complies with the current health and safety notes on inflatable play, BSEN14960 has been adopted where appropriate on the above inspection report.

If the above equipment is an inflatable used for part of a game, I deem this item fit for purpose.

All anchor points must be used to secure the unit to the ground at all times.